

**FSKY**

# Xact

**H5701**  
Series Servo

**FEATURES**

- For F3K DLG
- 6.5g weight & 6mm thick
- Speedy Response
- Incomparable Torque Performance
- High Precision with Zero Slop
- The Best Positioning Accuracy of Central Point
- Built-in Hall Sensor
- Programmable Travel Angle
- Robust CNC Aluminum Case with Metal Gear

**SPECIFICATIONS**

- Dimensions: 29.2\*6\*23mm (L\*W\*H)
- Weight: 6.5g
- Voltage range: 3.5-8.4V (6.0-8.4V is recommended)
- Telemetry: Current / Temperature / Travel Angle
- Frequency: 1520us/333Hz | 760us/700Hz
- Dead Band: 0.001ms
- Bearing Ball / Gear: Metal
- Motor Type: Coreless
- Servo Horn Spline:  $\Phi$ 4 15T
- Programmable: Yes, Travel Angle
- Port Type: FP2 (FBUS) / PWM / SBUS

	@ 6.0V	@ 7.4V	@ 8.4V
Torque (kg*cm/oz*in)	1.60/22.2	2.0/27.8	2.30/31.9
Speed (S/60Deg)	0.13	0.11	0.09






FSKY Electronic Co., Ltd.  
Made in China